

ACJW-LED

Construction:

- Steel housing and chassis
- Diffuser is .10" thick extruded white acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Center lockup - hardware included
- Open top and bottom
- Horizontal or vertical mounting
- Optional battery backup
- ADA compliant
- Build America, Buy America Act Compliant
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components
- **For WET listed version see MANW Series**

Type:	
Job Name:	



ACJW-16-LED

Height - 16"
Width - 7 1/8"
Depth - 4"

ACJW-24-LED

Height - 24"
Width - 7 1/8"
Depth - 4"



ORDERING INFORMATION

Example: ACJW-16-LED-O2C-4-B1-WSA

ACJW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
16-LED	O2C	18	2420	0-10v	NO	2 3000K 3 3500K 4 4000K		B1 Satin Black M13 Anod Silver T4 Shimmer Gray T6 Pewter W2 Gloss White W1 Yolk White Z1 Satin Bronze Z3 Text Bronze M17 Metallic Brass P1 Chrome* P2 Brushed Alum	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) Optional Voltage -347V Input voltage to 347v Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes
24-LED	O2C	18	2420	0-10v	NO					

* Interior Use Only



28435 Industry Drive., Valencia, California 91355
800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
www.lightwayind.com • sales@lightwayind.com

