

# RBSW-LED

## Construction:

- Steel housing and chassis
- Diffuser is .080" thick white smooth polycarbonate
- Optional alabaster acrylic is .080" thick

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Extension arms mount to standard J-Box
- Solid bottom cover is standard; optional lens
- Closed top eliminates upward light pollution
- Optional battery backup for RBSW 24 & 32
- Build America, Buy America Act Compliant
- UL and CUL listed **WET** location
- LED Components
  - Replaceable Module
  - CRI > 90
  - Dimming (10% or 1%)
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



Cage (A)

Cage (B)

<b>RBSW-16</b>	<b>RBSW-24</b>	<b>RBSW-32</b>
Height - 16"	Height - 24"	Height - 32"
Width - 7"	Width - 9"	Width - 9"
Ext. - 9"	Ext. - 12"	Ext. - 12"



## ORDERING INFORMATION

Example: RBSW-24-LED-O2C-3-Z3-WSP

## RBSW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
16-LED	O4B18	18	2420	0-10v	NO	2 3000K	A	B1 Satin Black	WSP White Smooth Polycarbonate	DIM LED dimming driver (0 - 10v) Dimming to 10% (Included)
	O4A	24	3200	0-10v	NO	3 3500K	B	B2 Text Black		
						4 4000K	X	Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige		
24-LED	O4B18	18	2420	0-10v	NO			Optional Lens Material (see Price List)	AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster	WBL White Bottom Lens Z1 Photocell -01 120 volt -02 277 volt
	O4B36	36	4840	0-10v	NO					
32-LED	O3B	22	3000	0-10v	NO			Optional (See Price List)	Battery Backup Options RBSW-24 & RBSW-32 (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes	
	O6B	44	6000	0-10v	NO			M17 Brass Powder		



28435 Industry Drive., Valencia, California 91355  
800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
www.lightwayind.com • sales@lightwayind.com

