

# ORSW-LED

## Construction:

- Small-hole perforated steel shield; steel chassis
- Diffuser is white textured polycarbonate behind perforated metal shield

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Keyhole slots or center lockup for standard J-box
- Custom cage styles available
- Open top and bottom for up and down light
- ADA compliant
- Optional Battery Backup
- Build America, Buy America Act Compliant
- UL and CUL listed **DAMP** location
- LED Components
  - Replaceable Module
  - CRI > 90
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



### ORSW-11-LED

Height - 11"  
Width - 10"  
Depth - 4"

### ORSW-16-LED

Height - 15.5"  
Width - 14"  
Depth - 4"



## ORDERING INFORMATION

Example: ORSW-11-LED-F1P-4-W1-POS

## ORSW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 3 3500K 4 4000K				
11-LED	F1H	9	1400	0-10v	YES				POS Small Perforated Steel Shield with White Textured Polycarbonate	<b>DIM</b> LED dimming driver (0 - 10v) <b>DIMLD</b> Line Voltage /TRIAC/ELV/120v See Resource Page  <b>ES</b> Energy Star listed components <b>ES</b> Energy Star listed components <b>T24</b> Title 24/JA8 Compliant (F10 & F1P configuration only)
	F1O	10	863	TRIAC/ELV	YES					
	F1P	15	1361	TRIAC/ELV	YES					
	O2A	12	1600	0-10v	NO					
	F1J	20	2820	0-10v	YES					
16-LED	F1H	9	1400	0-10v	YES				<b>OCCHFB</b> Concealed Occupancy Sensor (O2A Configuration Only) See Sensor Resource Sheet  <b>Battery Backup Options</b> (Available with 0-10v only) <b>BB10</b> 10 Watts (1170lm) for 90-Minutes	
	F1P	15	1361	TRIAC/ELV	YES					
	O2A	12	1600	0-10v	NO					
	O2C	18	2420	0-10v	NO					
								<b>B1</b> Satin Black <b>M13</b> Anod Silver <b>T4</b> Shimmer Gray <b>T6</b> Pewter <b>W2</b> Gloss White <b>W1</b> Yolk White <b>Z1</b> Satin Bronze <b>Z3</b> Text Bronze  <b>Optional Finishes</b> (see Price List) <b>M17</b> Brass Powder <b>P2</b> Brushed Alum <b>P9</b> Brushed Nickel		



28435 Industry Drive., Valencia, California 91355  
800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201  
www.lightwayind.com • sales@lightwayind.com

