

BRAW-LED

Construction:

- Steel housing and chassis
- Seamless one piece .060" thick white smooth polycarbonate diffuser which includes the top and bottom

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Keyhole slots for standard J-box
- Top and bottom lens allows for up and down light
- Custom printed lens styles available
- ADA compliant
- Optional battery backup
- Optional Anti-Ligature Compliant
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



OPTIONAL WHP LENS



BRAW-11

Height - 11"
 Width - 8 1/4"
 Depth - 3 1/2"

ORDERING INFORMATION

Example: **BRAW-11-LED-F1H-4-B1-WTP**

BRAW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
11-LED	F1H	9	1400	0-10v	YES	2 3000K 3 3500K 4 4000K		B1 Satin Black	WSP White Smooth Polycarbonate	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page
	F1O	10	863	TRIAC/ELV	YES			Z1 Satin Bronze		
	F1P	15	1361	TRIAC/ELV	YES			Z3 Text Bronze		
	O2A	12	1600	0-10v	NO			W1 Yolk		
	F1J	20	2820	0-10v	YES			W2 Gloss White		
							W3 Text White	Optional Lens Material (see Price List)		ES Energy Star listed components
							B2 Text Black	WHP White Hexagon Polycarbonate		T24 Title 24/JA8 Compliant (F10 & F1P configuration only)
							T4 Shimmer Gray	WXP Custom Polycarbonate		AL Anti-Ligature
							M13 Anod Silver			OCCHFB Concealed Occupancy Sensor (O2A Configuration Only) See Sensor Resource Sheet
							T6 Pewter			Battery Backup Options (Available with 0-10v only)
							W13 Pearl Beige			BB10 10 Watts (1170lm) for 90-Minutes
							Optional (See Price List)			
							P1 Chrome			
							P2 Brushed Alum			
							P9 Brushed Nickel			
							M16 Antique Brass			



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 www.lightwayind.com • sales@lightwayind.com

