

FERH-LED

Construction:

- Spun 3-step steel pan
- Diffuser is white smooth acrylic


Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Keyhole slots for standard J-Box installation
- Optional battery backup
- Build America, Buy America Act Compliant
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



FERH-24-LED
 Height - 15-1/2"
 Width - 24"
 OAH - 24"



ORDERING INFORMATION

Example: FERH-24-LED-08C-4-Z1-WSA-1SLM45-15.5" OAH

FERH

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
24-LED	L1A	36	4000	0-10v	NO	2 3000K 3 35000 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WSA White Smooth Acrylic	(Suspension Systems) Please list Over All Height 1SLM45 -Single Stem 45 degree swivel DIM LED dimming driver (0 - 10v) OCCHFA Concealed Occupancy Sensor <i>See Sensor Resource Sheet</i> Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes
	O8C	72	9680	0-10v	NO			Optional (See Price List) M17 Brass Powder P9 Brushed Nickel		



28435 Industry Drive., Valencia, California 91355
 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 www.lightwayind.com • sales@lightwayind.com

