

ARBC-LED

Construction:

- Steel housing and chassis
- Diffuser is .080" thick white smooth or textured polycarbonate.

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Center lockup – hardware included
- Inner lens retainer to secure lens panels to frame
- **Build America, Buy America Act Compliant**
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:

Job Name:



ARBC-10-LED

Height - 10"

Width - 10"

Depth - 4"



ORDERING INFORMATION

Example: ARBC-10-LED-F1P-4-Z3-WTP

ARBC

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
10-LED	F1L	9	1400	0-10v	YES	2 3000K 3 3500K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WTP White Textured Polycarbonate WSP White Smooth polycarbonate	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page ES Energy Star listed components T24 Title 24/JA8 Compliant (F10 & F1P configuration only) 90CRI Consult Factory OCCHFA Concealed Occupancy Sensor See Sensor Resource Sheet
	F1O	10	863	TRIAC/ELV	YES					
	F1P	15	1361	TRIAC/ELV	YES					
								Optional (See Price List) M17 Brass Powder P2 Brushed Alum P9 Brushed Nickel		



28435 Industry Drive., Valencia, California 91355
800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
www.lightwayind.com • sales@lightwayind.com



Revision: 04/17/2025