

PDLC-LED

Construction:

- Steel housing and chassis
- Bottom lens is white frosted acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Ceiling mount only
- Surface mount with appropriate cable whip.
- Optional **SBC** small box cover to mount to 2 x 4 box opening oriented to match fixture's linear dimension
- Optional **LBC** large box cover to mount to standard extension box
- Optional battery backup
- Build America, Buy America Act Compliant
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI >90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



PDLC-24-LED	PDLC-36-LED	PDLC-47-LED
Height - 3"	Height - 3"	Height - 3"
Length - 24"	Length - 36"	Length - 47"
Width - 2 1/2"	Width - 2 1/2"	Width - 2 1/2"



ORDERING INFORMATION

Example: **PDLC-36-LED-O3C-4-T4-WSA**

PDLC

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
24-LED	O2C	18	2420	0-10v	NO	2 3000K 3 3500K 4 4000K	B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige Optional (See Price List) M17 Brass Powder M16 Antique Brass P2 Brushed Alum P9 Brushed Nickel	WFA White Frosted Acrylic	SBC Small box cover standard 2 x 4 junction box (5" wide x 3" high) LBC Large box cover standard junction box (5" wide x 6" high) DIM LED dimming driver (0 - 10v) Battery Backup Options Available in 36" and 48" only BB08 Battery backup unit providing 8 Watts (1080lm) for 90-Minute	
36-LED	O3C	27	3630	0-10v	NO					
47-LED	O4C	36	4840	0-10v	NO					



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 www.lightwayind.com • sales@lightwayind.com

