

# VLXV-LED

## Construction:

- Steel chassis and end caps
- Diffuser is white smooth acrylic or optional clear prismatic acrylic
- clear prismatic acrylic

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Mounts to standard J-Box with slotted anchor holes
- Optional battery backup (36" or 48" only)
- Spring end caps for no visible fasteners
- Build America, Buy America Act Compliant
- UL and CUL listed **DAMP** location
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components



Type:	
Job Name:	



Length - 24" - 36" - 48" - 60" - 72"  
 Height - 4 1/4"  
 Depth - 4 1/4"



## ORDERING INFORMATION

Example: VLXV-36-LED-03C-2-W1-WSA

VLXV

Size	LED	Watts	Source Lumens	Dimming	Energy Star	Kelvin	Cage	Finish	Diffuser	Options
24-LED	O2C	18	2420	0-10v	NO	2 3000K 4 4000K		<b>B1</b> Satin Black <b>B2</b> Text Black <b>Z1</b> Satin Bronze <b>Z3</b> Text Bronze <b>W1</b> Yolk White <b>W2</b> Gloss White <b>W3</b> Text White <b>T4</b> Shimmer Gray <b>M13</b> Anod Silver <b>T6</b> Pewter <b>W13</b> Pearl Beige  Optional (See Price List) <b>M17</b> Brass Powder	<b>WSA</b> White Smooth Acrylic  <b>Optional Lens Material</b> (see Price List) <b>CPA</b> Clear Prismatic Acrylic	<b>DIM</b> LED dimming driver (0 - 10v) <b>DIMLD</b> Line Voltage /TRIAC/ELV/120v Consult Factory  <b>90CRI</b> Consult Factory <b>T24</b> Title 24/JA8 Compliant (F1Y configuration only)  <b>Battery Backup Options</b> (Available with 0-10v only) <b>BB10</b> 10 Watts (1170lm) for 90-Minute
	F1Y	30	3235	TRIAC/ELV	YES					
36-LED	O3C	27	3630	0-10v	NO	Optional 3 3500K				
48-LED	O8C	72	9680	0-10v	NO					



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com



Revision: 09/09/2024