

TLOW-LED

Construction:

- Steel housing and chassis
- Clear Smooth Acrylic Lens
- Optional White Frosted Acrylic Lens


Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Integral mounting plate
- All aluminum construction (painted finish only)
- Optional photocell - (21) specify voltage 120v or 277v
- Optional battery backup
- Dark Sky compliant
- Build America, Buy America Act Compliant
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



TLOW-8-LED

Height - 8"
Width - 8 1/4"
Depth - 6"

TLOW-10-LED

Height - 10"
Width - 10 1/4"
Depth - 7 1/4"

TLOW-12-LED

Height - 13 3/4"
Width - 12 1/4"
Depth - 8 1/2"



ORDERING INFORMATION

Example: TLOW-10-LED-O2A-4-W2-WSA-42

TLOW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
8-LED	O1A	6	800	0-10v	NO	1 2700K 2 3000K 3 3500K 4 4000K 5 5000K		B1 Satin Black	CSA Clear Smooth Acrylic WFA White Frosted Acrylic	DIM LED dimming driver (0 - 10v)
	O2A	12	1600	0-10v	NO			B2 Text Black		
10-LED	O1A	6	800	0-10v	NO			Z1 Satin Bronze		
	O2A	12	1600	0-10v	NO			Z3 Text Bronze		
12-LED	O1B	8	1000	0-10v	NO			W1 Yolk White		
	O2B	15	2000	0-10v	NO			W2 Gloss White		
	O3B	22	3000	0-10v	NO			T4 Shimmer Gray		
								M13 Anod Silver		
								T6 Pewter		
								W13 Pearl Beige		
						Optional (See Price List)				
						M17 Brass Powder				
						P2 Brushed Alum				
									42 All Aluminum Construction	
									21 Photocell - See Notes	
									-01 120 volt	
									-02 277 volt	
									OCCHFA Concealed Occupancy Sensor	
									Battery Backup Options (Available with 0-10v only)	
									BB10 10 Watts (1170lm) for 90-Minutes	



28435 Industry Drive., Valencia, California 91355
800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
www.lightwayind.com • sales@lightwayind.com

