

SUTC-LED

Construction:

- Steel pan
- Diffuser is frosted marbleized glass

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Keyhole slots for standard J-Box – hardware included
- Optional battery backup
- UL and CUL listed **DAMP** location optional occ
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



SUTC-16
 Height - 7 ¼"
 Diameter - 15 ½"



ORDERING INFORMATION

Example: SUTC-16-LED-F1P-4-Z3-FMG

SUTC

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
16-LED	F1L	9	1400	0-10v	YES	1 2700K 2 3000K 3 3500K 4 4000K 5 5000K	B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige M17 Brass Powder Optional (See Price List) P2 Brushed Alum P9 Brushed Nickel	FMG Frosted Marbleized Glass	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page ES Energy Star listed components T24 Title 24/JA8 Compliant (F1P & F1Q configuration only) OCCHFA Concealed Occupancy Sensor See <i>Sensor Resource Sheet</i> Battery Backup Options (Available with 0-10v only)	
	O3B	22	3000	0-10v	NO					
	F1P	15	1361	TRIAC/ELV	YES					
	F1K	13	2115	0-10v	YES					
	F1Q	23	2057	TRIAC/ELV	YES					



28435 Industry Drive., Valencia, California 91355
 800-325-4448 /661-257-0286
 www.lightwayind.com • sales@lightwayind.com

