

MENW-600-LED

Construction:

- Steel housing and chassis
- Diffuser UV-stabilized, high impact resistant, 100% DR acrylic

Light Source:

- LED
- Dimming to 10% **Included**


Notes:

- Integral mounting plate; keyhole slots
- Top and bottom white acrylic lens - standard
- Optional photocell (21) increases fixture depth 1 1/2"
- Optional battery backup
- Optional lens cover (NCL) prevents up/down light
- ADA compliant
- Build America, Buy America Act Compliant
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components
- You may also like the [MERW](#) or [MANW](#) Series


Type:	
Job Name:	



DESIGN OPTIONS



MENW-A




MENW-B




MENW-C



MENW-D



MENW-E





MENW-F

Fixture Overall Dimensions

- "H" - 12" - 16" - 18" - 26" - 38" - 50"
- "W" - 6 1/2"
- "D" - 4"
- "MC" - 6" - 8" - 9" - 13" - 19" - 25"

- See 900 or 1100 Series for other width options



28435 Industry Drive., Valencia, California 91355
 800-325-4448 / 661-257-0286
www.lightwayind.com • sales@lightwayind.com



MENW-600-LED

ORDERING INFORMATION

Example: MENW-616-LED-O1C-3-D-Z1-WSA

MENW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
612-LED	F1H	9	1400	0-10v	YES	2 3000K 3 3500K 4 4000K	A	B1 Satin Black	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v Consult Factory Z1 Photocell - Specify voltage 01 - 120 volt 02 - 277 volt NCL Aluminum Lens Cover - <i>See Notes</i> ES Energy Star listed components 39 J-Box with knockouts on all sides Battery Backup Options <i>(Available with 0-10v only)</i> BB10 10 Watts (1170lm) for 90-Minutes
	F1P	15	1361	TRIAC/ELV	YES		B	B2 Text Black		
616-LED	O1C	9	1210	0-10v	NO		D	Z1 Satin Bronze		
618-LED	O2A	12	1600	0-10v	NO		C	Z3 Text Bronze		
626-LED	O2C	18	2420	0-10v	NO		E	W1 Yolk White		
626-LED	F1Y	30	3235	TRIAC/ELV	YES		F	W2 Gloss White		
638-LED	O3C	27	3630	0-10v	NO		X	W3 Text White		
650-LED	O4C29	29	3412	0-10v	NO			T4 Shimmer Gray		
	O4C	36	4840	0-10v	NO			M13 Anod Silver		
							W13 Pearl Beige			
							Optional (See Price List) M17 Brass Powder P2 Brushed Alum P9 Brushed Nickel			



28435 Industry Drive., Valencia, California 91355
 800-325-4448 /661-257-0286
 www.lightwayind.com • sales@lightwayind.com

