

PLPC-LED

Type:	
Job Name:	

Construction:

- Steel pan and rings
- Diffuser is white smooth acrylic
- Optional high efficiency white smooth acrylic lens designed for LED light source (WSAHE)

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Keyhole slots for standard J-box
- Optional battery backup - Requires 1 3/4" extension ring
- Build America, Buy America Act Compliant
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components



PLPC-12-LED

Height - 3 1/4"
w/ext ring - 5 1/4"
Diameter - 12"

PLPC-15-LED

Height - 3 1/4"
w/ext ring - 5 1/4"
Diameter - 15"

PLPC-21-LED

Height - 4 3/8"
w/ext ring - 5 1/4"
Diameter - 21 1/4"



ORDERING INFORMATION

Example: PLPC-15-LED-F1K-4-T6-WSA

PLPC

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
12-LED	F1L	9	1400	0-10v	YES	2 3000K 3 3500K 4 4000K		T6 Pewter W2 Gloss White Z1 Satin Bronze Z3 Text Bronze W1 Yolk W3 Text White B1 Satin Black B2 Text Black T4 Shimmer Gray M13 Anod Silver W13 Pearl Beige	WSA White Smooth Acrylic Optional Lens Material (see Price List) WSAHE White Smooth Acrylic High Efficiency	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page ES Energy Star listed components T24 Title 24/JA8 Compliant (F10, F1P & F1Q configuration only) OCCHFA Concealed Occupancy Sensor See Sensor Resource Sheet Battery Backup Options (Requires 1 3/4" extension ring) (Available with 0-10v only) PLPC-15 and 21 only BB10 10 Watts (1170lm) for 90-Minutes
	F1O	10	863	TRIAC/ELV	YES					
	F1P	15	1361	TRIAC/ELV	YES					
15-LED	F1K	13	2115	0-10v	YES					
	F1P	15	1361	TRIAC/ELV	YES					
	F1Q	23	2057	TRIAC/ELV	YES					
	F1R	28	4015	0-10v	YES					
21-LED	L1A	36	4000	0-10v	NO					



28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
www.lightwayind.com • sales@lightwayind.com

