

Type:

Job Name:

Construction:

- Steel construction
- Diffuser is white smooth acrylic

Light Source:

- LED
- Dimming to 10% **Included**
- 90CRI

Notes:

- Canopy mounts to standard "J-Box"
- Custom mounting heights available
- Single ridge 15 degree swivel stem standard (1S15)
Optional cord or cable mounting, see options
- Optional battery backup, requires oversized canopy with 1AC-__ or 1S15 mounting only.
- Build America, Buy America Act Compliant
- UL and CUL listed **DAMP** location
- 5-Year Warranty on LED Components
- Universal 120/277 volt standard



WWXH 12 - 14 - 16 - 18 - 20
Height: 12" 14" 16" 18" 20"
Diameter: 12" 14" 16" 18" 20"
OAH: 24" 24" 24" 24" 36"



ORDERING INFORMATION

Example: WWXH-12-LED-O4A-4-Z1-WSA-1S15-24"OAH

WWXH

Size	LED	Watts	Source Lumens	Dimming	Energy Star	Kelvin	Cage	Finish	Diffusers	Options
						2 3000K 3 3500K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WSA White Smooth Acrylic	(Suspension Systems) Please list Over All Height 1S15 - Single 15 ° Swivel Stem (Standard) 1SLM45 - Single Stem 45 degree swivel (field adjustable) WSJ - White "SJ" Cord BSJ - Black "SJ" Cord 1AC__ - Aircraft Cable w/SJ cord WSJ - White "SJ" Cord BSJ - Black "SJ" Cord DIM LED dimming driver (0 - 10v) Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes
12-LED	O4A	24	3200	0-10v	NO					
	1E26		0	TRIAC/ELV	NO					
14-LED	O4A	24	3200	0-10v	NO					
	1E26		0	TRIAC/ELV	NO					
16-LED	O4A	24	3200	0-10v	NO					
	O4B	29	4000	0-10v	NO					
18-LED	O4A	24	3200	0-10v	NO					
	O4B	29	4000	0-10v	NO					
	O4C	36	4840	0-10v	NO					
20-LED	O4A	24	3200	0-10v	NO					
	O4B	29	4000	0-10v	NO					
	O4C	36	4840	0-10v	NO					



28435 Industry Drive., Valencia, California 91355
800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
www.lightwayind.com • sales@lightwayind.com

