

# FLPA-LED

## Construction:

- Steel housing and chassis
- Diffuser is White Frosted Acrylic or optional Clear Smooth Acrylic

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- ½" NPT knuckle mounts to junction box or ground fitter
- Optional Photocell (21)
- Optional Ground Fitter (84)
- UL and CUL listed **WET** location
- Build America, Buy America Act Compliant
- LED Components
  - Replaceable Module
  - CRI > 90
  - Voltage 120 - 208 - 240 - 277
  - 5-Year Warranty on LED Components

<b>Type:</b>	
<b>Job Name:</b>	



Shown as White Frosted Acrylic

### FLPA-5

Height - 4 ½"

Width - 8 ½"

Depth - 2 ½"



## ORDERING INFORMATION

Example: FLPA-5-LED-O2A16-4-Z1-WFA

### FLPA

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
5-LED	O2A16	16	2122	0-10v	NO	2 3000K		W1 Yolk	WFA White Frosted Acrylic	DIM LED dimming driver (0 - 10v)
						3 3500K		W2 Gloss White		
						4 4000K		W3 Text White		
						5 5000K		B1 Satin Black		
								B2 Text Black		
							Z1 Satin Bronze			
							Z3 Text Bronze			
							T4 Shimmer Gray			
							M13 Anod Silver			21 Photocell - Specify voltage
							T6 Pewter			01 - 120 volt
							W13 Pearl Beige			02 - 277 volt
										24 24" Extension Arms
										84 Ground Fitter
										FH Fixed Hood



28435 Industry Drive., Valencia, California 91355  
 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
 www.lightwayind.com • sales@lightwayind.com

