

# DELW-LED

## Construction:

- Steel housing and chassis
- Diffuser is .10" thick extruded white acrylic

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Center lockup - hardware included
- Open top and bottom
- Horizontal or vertical mounting
- Optional battery backup
- ADA compliant
- Build America, Buy America Act Compliant
- UL and CUL listed **DAMP** location
- LED Components
  - Replaceable Module
  - CRI > 90
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components
- **For WET listed version see MANW Series**

Type:	
Job Name:	



### DELW-16-LED

Height - 16"  
Width - 7 1/8"  
Depth - 4"

### DELW-24-LED

Height - 24"  
Width - 7 1/8"  
Depth - 4"



## ORDERING INFORMATION

Example: DELW-16-LED-O2C-4-P1-WSA

### DELW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
16-LED	O2C	18	2420	0-10v	NO	2 3000K 3 3500K 4 4000K		B1 Satin Black M13 Anod Silver T4 Shimmer Gray T6 Pewter W2 Gloss White W1 Yolk White Z1 Satin Bronze Z3 Text Bronze M17 Metallic Brass P1 Chrome* P2 Brushed Alum	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v)
24-LED	O2C	18	2420	0-10v	NO			* Interior Use Only		Optional Voltage -347V Input voltage to 347v  <b>Battery Backup Options</b> (Available with 0-10v only) <b>BB10</b> 10 Watts (1170lm) for 90-Minutes



28435 Industry Drive., Valencia, California 91355  
800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201  
www.lightwayind.com • sales@lightwayind.com

