

AVAW-LED

Construction:

- Steel housing and chassis
- Diffuser is .080" thick white smooth or textured polycarbonate.
- Optional alabaster lenses are .080" thick acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Center lockup – hardware included
- Custom cage styles available
- ADA compliant
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Dimming (10% or 1%)
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



AVAW-10

Height - 10"
Width - 14"
Depth - 4"



ORDERING INFORMATION

Example: AVAW-10-LED-O1A-3-W1-WTP

AVAW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
10-LED	O1A	6	800	0-10v	NO	2 3000K 4 4000K		B1 Satin Black M13 Anod Silver T4 Shimmer Gray T6 Pewter W2 Gloss White W1 Yolk White Z1 Satin Bronze Z3 Text Bronze Optional Finishes (see Price List) P0 Polished Brass* P1 Chrome* P2 Brushed Alum P9 Brushed Nickel M16 Antique Brass * Interior Use Only	WTP White Textured Polycarbonate WSP White Smooth polycarbonate Optional Lens Material (see Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster	DIM LED dimming driver (0 - 10v) 90CRI Consult Factory Optional Voltage -347V Input voltage to 347v
						Optional 3 3500K				



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

