

ATLW-LED

Construction:

- Steel housing and chassis
- Diffuser is .10" thick extruded white acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Center lockup - hardware included
- Open top and bottom
- Horizontal or vertical mounting
- Optional battery backup
- ADA compliant
- Build America, Buy America Act Compliant
- UL and CUL listed DAMP location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

- **For WET listed version see MANW Series**

ATLW-16-LED

Height - 16"
Width - 7 1/8"
Depth - 4"

ATLW-24-LED

Height - 24"
Width - 7 1/8"
Depth - 4"

Type:	
Job Name:	



ORDERING INFORMATION

Example: ATLW-16-LED-O2C-4-B1-WSA

ATLW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 3 3500K 4 4000K		B1 Satin Black M13 Anod Silver T4 Shimmer Gray T6 Pewter W2 Gloss White W1 Yolk White Z1 Satin Bronze Z3 Text Bronze M17 Metalic Brass Optional (See Price List) P2 Brushed Alum	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) Optional Voltage -347V Input voltage to 347v Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes
16-LED	O2C	18	2420	0-10v	NO					
24-LED	O2C	18	2420	0-10v	NO					



28435 Industry Drive., Valencia, California 91355
800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
www.lightwayind.com • sales@lightwayind.com

